

## Genexis FiberTwist

### P2000-Series Point-to Point (PtP)

Compact network demarcation



Providing Gigabit fiber connectivity to any desired location in the home, is one of today's major challenges.

With the endless variety of different deployment scenarios and end-user requirements, this calls for a flexible and scalable connectivity solution.

With the FiberTwist product range, Genexis introduces a unique broadband connectivity solution that redefines size, ease of installation and flexibility for the distribution of fiber bandwidth throughout the entire home.

#### Key features

- Compact, fully managed Point-to-Point network demarcation
- A flexible solution matching both single-dwelling and multi-dwelling deployment scenarios
- Patented FiberTwist click-on interface on the FTU or Bracket, enabling trouble-free, DIY end-user installation
- Flexible management via TR-069, CLI, DHCP/TFTP and SNMP
- Optional integrated CATV receiver
- Up to 4 Gigabit LAN ports to connect external devices, such as a Residential Gateway and various Layer 2 services
- LED dimming
- Wall junction box compatible

#### A perfect fit for every deployment scenario

The Genexis FiberTwist product family has been developed in such a way that it can be integrated into various deployment models, including single-dwelling and multi-dwelling scenarios.

Using products from the FiberTwist FTU family, the demarcation point can be extended to any desired location in the home, enabling easy access and installation of services.

Its small size (110 x 110 x 46 mm) makes the FiberTwist a perfect fit in any environment, be it a living room, metering cabinet or basement.



# Product features and specifications

## Genexis FiberTwist P2000-series Point-to Point (PtP)

### General specifications

Dimensions (H x W x D)	110x110x46 mm
Weight (without on CATV)	176 g
Weight (with CATV)	225 g
Power supply voltage	12 Vdc ± 5%

### Power consumption

P2110	typ. 1.8 W
P2410	typ. 4.2 W
P2420	typ. 6.0 W
Operating temperature	0 - 40 °C
Storage temperature	0 - 70 °C

### WAN interface

Tx wavelength	1310 nm
Rx wavelength**	1490/1550 nm
Optical output range	-9 ... -3 dBm
Optical input range	-23 ... -3 dBm

### Network interface

Single mode fiber (ITU-T G.657)  
 SC/APC connector  
 Up to 20 km range  
 Compliant with 1000BASE-BX20-U  
 Compliant with 100BASE-BX20-U  
 Auto sensing 1Gb/s and 100Mb/s

### Layer 2 features

Support Jumbo frames (up to 9K)  
 Managed Quality of Service (QoS)  
 Network Terminator  
 · Remote port enabling/disabling  
 · Remote per-port rate shaping  
 · Up to 64 VLANs or 802.1q transparent  
 · Q-in-Q (PVID 88a8)  
 Media Converter  
 · WAN link state forwarding  
 · WAN to LAN link speed following

### LAN interfaces

Up to 4 1000/100/10Base-T RJ45 interfaces  
 LED indicators for link and activity

### CATV \*

Wavelength	1550 nm
Optical input range	-8 ... 0 dBm
RF output impedance	75 Ω
RF flatness	±1 dB
Output return loss	14 dB
RF output level (AGC)	80 ± 1 dBμV
AGC working range	-8 ... 0 dBm
RF frequency range	47 - 875 MHz
Slope / tilt	2 ... 5 dB
CNR min	45 dB@-8 dBm
CSO / CTB	max -55 dBc
Spurious to carrier	max -55 dBc
Remote enabling of CATV	

### User interfaces

1 x Unlock button  
 1 x Reset button \*\*\*  
 1 x LED dimming button \*\*\*  
 1 or 4x LAN interface  
 1 x Power connector  
 1 x CATV output coaxial F-female \*  
 1x Telephone FXS/RJ11 port \*

### Voice features\*

SIP based Voice-over-IP  
 G.711 A-law / μ-law codec  
 G.729 codec  
 5 REN support  
 Line Echo Cancellation  
 DTMF: In-band, RFC2833, SIP-Info  
 Class 5 features

\* Applicable to selected models only

\*\* The WAN receiver is wideband. In case it is combined with CATV it is sensitive to 1490nm only

\*\*\* Applicable to Network Terminator models only

### Management

Network Terminator  
 · TR-069, TR-181  
 · GAPS (7.0 and higher)  
 · CLI  
 · DHCP/TFTP  
 · IEEE 802.3ah OAM in passivemode:  
 · Discovery  
 · Loopback  
 · Fault notification (dying gasp)  
 Media Converter  
 · HTTP  
 · IEEE 802.3ah OAM in passive mode:  
 · Discovery  
 · Loopback  
 · Fault notification (dying gasp)  
 Remote monitoring  
 · CATV input signal  
 · (Calculated) RF output

### Emissions and safety regulations

CE approved, FCC on request  
 Safety:  
 · IEC EN 60950 or IEC EN 62368-1  
 Laser safety:  
 · IEC EN 60825-1: Class 1 laser  
 Emissions & Immunity:  
 · EN 55032/CISPR 32:2008, Class B  
 · EN 55024  
 RoHS/WEEE marking:  
 · Compliant with 2011/65/EU

### Status LEDs

Power  
 Fiber uplink status/activity  
 CATV status \*  
 Telephony status \*



## Genexis FiberTwist P2000-Series product models

Model	Type	WAN (Mbps)	LAN interface	Wavelength			
				Tx	Rx	Voice port (FXS)	CATV
FiberTwist-P2110	Media converter	1000/100	1x	1310 nm	1490 nm & 1550 nm	-	-
FiberTwist-P2410	Network terminator	1000/100	4x	1310 nm	1490 nm & 1550 nm	-	-
FiberTwist-P2411	Network terminator	1000/100	4x	1310 nm	1490 nm	-	-
FiberTwist-P2414*	Network terminator	1000/100	4x	1310 nm	1490 nm	Yes	
FiberTwist-P2420	Network terminator	1000/100	4x	1310 nm	1490 nm	-	1550 nm

\* Available from Q3 2019

Note: Not every listed feature may be included in the shipping product. We reserve the right to make changes of technical specifications, housing or design without prior notice.