



Genexis Elite HX40

Elite Series

Wi-Fi 6 Residential Gateway with 2.5GE



In the era of faster connectivity, your customers home deserve the best. Our Elite Series is the answer for this, offering speeds of 2.5 Gbps and beyond. No more buffering, no more lag.

But it's not just about speed. A router should match your lifestyle: sleek design, sustainable, and effortless usability by both end-user as operator. The Elite Series embodies these ideals.

Key features

- 802.11ax (Wi-Fi 6)
- Wi-Fi EasyMesh™
- AX3600: 1.200 Mbps (2.4 GHz) + 2.400 Mbps (5 GHz)
- High network speeds with 2.5GE WAN
- Easy setup/installation
- EasyTouch Pairing with selected Genexis extenders
- Analogue telephony support
- Desktop model and wall mount compatible
- Genexis CloudSight compatible

Sustainability features

- Designed for refurbishment
- Power consumption compliant to EU-CoC-BBE

Powerful, elegant, and accessible, it's the ultimate connectivity solution.

The Elite Series features Wi-Fi 6, Wi-Fi EasyMesh™, a 2.5GE WAN port and 2.5GE LAN port, it ensures that all connected network devices in the end-users home can run at their designated speeds without any limitations.

The start for the best WiFi experience with Wi-Fi EasyMesh™

The Elite is the perfect residential gateway to start, steer and create an EasyMesh network between different extenders.

Thanks to this EasyMesh network, end-users are able to fully experience the best WiFi connectivity throughout the whole home. Its steering capabilities keep the load balance of the network in mind to steer mobile devices to the correct access point (requires additional extenders).

Meaning that when the end-user freely walks through the home, it automatically connects to the most optimal access point at all time.

Resulting in the best possible WiFi experience for the end-user.



Product features and specifications

Genexis Elite HX40

General specifications

Dimensions (H x W x D)	165x214x80 mm
Weight	480 g
Power supply voltage	12 Vdc $\pm$ 2A
Operating temperature	0 - 40 °C
Storage temperature	-30 - 70 °C
Relative humidity	10% - 95%

Power consumption (EU-CoC-BBE)

Elite HX40	8.2 W Idle Mode
	9.5 W On Mode

WAN interface

1x 100/1000/2500 Base-T Ethernet RJ45

LAN interface

4x 100/1000 Base-T Ethernet RJ45

WLAN interface

4x4 MU-MIMO 802.11ax 2.4 GHz WiFi
4x4 MU-MIMO 802.11ax 5 GHz WiFi

Voice interface

1x FXS RJ11 port

USB interface

1x USB 2.0 port

User interfaces

Power connector
Power switch
Reset button
RGB status LED
End-user web based GUI

Wireless features

Wi-Fi MultiMedia (WMM)
Wi-Fi Protected Setup (WPS)
Wi-Fi Security (WPA2 and WPA3)
Wi-Fi EasyMesh™ R4
DFS and Radar Detection
Multiple SSID and hidden SSID
Guest network SSID

Ethernet features

IPv4 and IPv6 dual IP stack
VLAN (un)tagging, Q-in-Q, QoS
PPPoE, L2TP, IGMPv3

Gateway features

NAT/PAT, DHCP, DNS
NTP, RTSP
Stateful Packet Inspection Firewall (SPIF)
DMZ, uPnP, Port forwarding

Voice features

SIP based Voice-over-IP
G.711 / G.722 / G.723 codec
G.726 / G.729 codec
DTMF: In-band, RFC2833, SIP-info
3 REN support
Class 5 features

USB features

NTFS and FAT32 file system storage devices

Management and control

TR-069, TR369
TR-181, TR-104 data models
Command Line Interface (CLI)
Web based GUI
Genexis EasyWiFi App
Genexis CloudSight
Fail-safe firmware upgrade

Regulatory compliance

Radio Equipment Directive 2014/53/EU
EU-CoC-BBE power consumption
Energy Related Products Directive 2009/125/EC
CE Safety Directive 2014/35/EU
UKCA Safety Regulations 2016
RoHS and REACH Directive 2011/65/EU
ITU-T K.21 standard compliancy

Package content

Elite HX40
Wall mount
Power supply unit
Ethernet cable
Quick installation guide

Genexis Aura Series product models

Model	Uplink WAN (Mbps)	LAN (Mbps)		WLAN 4x4 2.4 GHz	WLAN 4x4 5.0 GHz	FXS	USB
Elite HX40	100/1000/2500	4x	100/1000	11ax	11ax	1x	1x

Note: No rights can be derived from this publication. Not every listed feature may be included in the shipping product. We reserve the right to make changes without prior notice.