



Genexis FiberTwist

FTU 1000-Series (Fiber Termination Unit)

Base plate with fiber management



The FiberTwist FTU can be used as the foundation for all Genexis FiberTwist active units. This includes those from both the Point-to-Point and GPON, XGS-PON families, as well as optical data and RFoG.

The compact form factor of the FiberTwist FTU has been specifically designed for fast, efficient and easy installation in any location.

FiberTwist is a unique FTTH connectivity solution that redefines size, ease-of-installation and flexibility for the distribution of fiber bandwidth throughout the home.

With FiberTwist, you only need one product to cover each and every deployment scenario in your network.

Key Features

- Compact Fiber Termination Unit (FTU) compatible with all FiberTwist active units
- Patented FiberTwist click-on interface enabling 100% trouble free, DIY active unit installation
- Suitable for patch cables and micro pipes of up to and including 10 mm
- · Fiber ingress options: top, bottom, back 2x
- · Fiber management with 2 strain relief options per fiber ingress
- · Option for either an SC/PC patch in connector or a gas blocker
- · Optional Quad-LC or Dual-SC connector with break-out plastic
- · Splice holders for up to 6 pigtails
- · Tamperproof sealable fiber management (warranty seal)
- · Pre-installed pigtail(s) optional
- Optional Blind Cover available to protect the installation until the active unit (NT) is installed

Good things come in small parcels

The FiberTwist comes in a super compact design of only 11 x 11 cm. Its patented Twist interface enables easy installation of active equipment as well as its fiber patch module. Furthermore, the FTU's fiber management system cleverly integrates all technical features one would expect of a professional FTU.

The FTU is capable of holding six fibers. One connects to the active unit, and up to four others are available at any time. For example: as backup fiber or when using a Quad-LC or Dual-SC connector in a patch-out scenario. A choice of six ingress ports provides maximum installation flexibility.

Product features and specifications

G

Genexis FiberTwist FTU 1000-Series

Dimensions (H x W x D)

FTU 110x110x19 mm
 With Blind Cover 110x110x40 mm
 With active unit 110x110x46 mm

Weight

FTU 89 gBlind cover 48 g

Mounting options

Wall junction box compatible

Safety regulations

- · CE IEC 62368
- · UL94HB flammability class
- · RoHS 3 and REACH compliant

Fiber management

Storage for 6 Fibers 4 fiber ingress points

1 patch port can accommodate:

· Quad-LC or Dual-SC connector

Sealable fiber management & strain relief

Fiber types supported:

G.657.A1/.A2/.B2/.B3

Attenuation Grade C, Return Loss Grade 1 (IEC 61753)

Compliant with ITU-T G.657.A2

12 mm (short) boot

Pre-installed pigtail(s) optional

Max. gas-blocker size $25 \times Ø15 \text{ mm}$

Pigtails*

Attenuation Grade C, Return Loss Grade 1 (IEC 61753)

Compliant with ITU-T G.657.A2

Accessories (supplied)

Mounting screws and plugs

Cable ties

Foam padding

Splice holders for:

- · 6 ANT splices
- 2 single fusion with splice sleeve max 3mm width splice nails

Warranty seal

SC/APC Twist connector

Installation guide (digital available)
Drilling template (digital available)

Accessories (optional)

Blind Cover (picture below):

- Finishes and protects the FTU until installation of the NT (active unit)
- * Applicable to selected models only, see table



FiberTwist FTU-1000



FiberTwist FTU-1100



Use case: with gas blocker



FiberTwist FTU-BlindCover



FiberTwist FTU-1111



FiberTwist FTU-1141



Use case: with thick patch cable



Customized FTU-BlindCover

Genexis FiberTwist FTU-1000 Series product models

Models	Models with pre-installed pigtail(s)	Patch- connector
FiberTwist FTU-1000	FiberTwist FTU-1100	-
FiberTwist FTU-1010	FiberTwist FTU-1111	SC/PC (blue) patch in
FiberTwist FTU-1020	FiberTwist FTU-1121	Dual-SC/APC (green) patch out
FiberTwist FTU-1040	FiberTwist FTU-1141	Quad-LC/APC (green) patch out with internal shutters and laser safety sticker
FiberTwist FTU-BlindCover	Provides dust protection for the fiber. Fits all FTU models	