

Genexis Home CX30

Home Series

Wi-Fi 6 Extender with 1GE



To meet the demand for higher capacity and broader coverage, your customers' homes deserve an extender that scales with their lifestyle.

Home CX30 pairs dual-band Wi-Fi 6 with Wi-Fi EasyMesh™ and adds extra LAN ports for flexible wired connections.

Paired with the Genexis Wi-Fi6 gateway, it integrates into a single mesh network, delivering consistent throughput and smooth roaming across the home. Whether wireless or wired backhaul, CX30 ensures every device performs without bottlenecks.

Key features

- · Compact size, flexible placement options
- · 802.11ax (Wi-Fi 6)
- Wi-Fi EasyMesh™
- · 2.4GHz (2x2) and 5GHz (3x3) radio design
- Easy setup/installation
- EasyTouch Pairing with selected Genexis devices
- · Genexis CloudSight compatible

Sustainability features

- · Power consumption compliant to EU-CoC-BBE
- · Housing made of 99% recycled plastics

Always the best WiFi experience with Wi-Fi EasyMesh $^{\text{\tiny TM}}$

When two (or more) Home CX30 devices are integrated in the same network, automatically an EasyMesh network is created between the installed Home CX30 devices.

Thanks to this EasyMesh network, end-users are able to fully experience the best WiFi connectivity throughout the whole home. Its mobile steering capabilities keep the load balance of the network in mind to steer the mobile devices to the correct access point.

Meaning that when the end-user freely walks through the home, it automatically connects to the most optimal access point at all

Resulting in the best possible WiFi experience for the end-user.

Product features and specifications

6.37 W On Mode



Genexis Home CX30

General specificationsUser iDimensions (H x W x D)110x110x110 mmPowerWeight approx.380 gResetPower supply voltage12 Vdc ± 1,5AWPS bOperating temperature0 - 40 °CRGB s

Storage temperature $$-30\mbox{ -}70\mbox{ }^{\circ}$C}$ Relative humidity $$10\%\mbox{ -}95\%$

Power consumptionHome CX30 5.84 W Idle Mode

WAN interface

1x 100/1000 Base-T Ethernet RJ45 port

LAN interface 2x 100/1000 Base-T Ethernet RJ45 ports

WLAN interface 2x2 MU-MIMO 802.11ax 2.4 GHz WiFi 3x3 MU-MIMO 802.11ax 5 GHz WiFi User interfaces
Power connector
Reset button
WPS button
RGB status LED

Wi-Fi MultiMedia (WMM)
Wi-Fi Protected Setup (WPS)

Wi-Fi Security (WPA2 and WPA3)

Wi-Fi EasyMesh™ R2
DFS and Radar Detection
Multiple SSID and hidden SSID
Guest network SSID

Ethernet features

IPv4 and IPv6 dual IP stack VLAN (un)tagging, Q-in-Q, QoS PPPoE, L2TP, IGMPv3 Management and control

SNMP

TR-069, TR-369 TR-181 data models

Command Line Interface (CLI)

Genexis CloudSight

Fail-safe firmware upgrade

Regulatory compliance

Radio Equipment Directive 2014/53/EU Energy Related Products Directive 2009/125/EC

CE Safety Directive 2014/35/EU RoHS and REACH Directive 2011/65/EU ITU-T K.21 standard compliancy

Package content

Home CX30
Power supply unit
Ethernet cable
Quick installation guide

Genexis Home CX30 product models

Model	Туре	Uplink WAN (Mbps)	L	.AN (Mbps)	WLAN 2x2 2.4 GHz	WLAN 4x4 5.0 GHz	
Home CX30	In-Home WiFi: wired extender/wireless extender	100/1000	2x	100/1000	11ax	11ax	

Note: Not every listed feature may be included in the shipping product. We reserve the right to make changes of technical specifications, housing or design without prior notice.